

Amendments to the Claims

Please cancel Claims 7 and 15 without prejudice to or disclaimer of the subject matter recited therein.

Please amend Claims 1, 4-6, 8 and 10-14 to read as follows.

1. (Currently amended) A recording apparatus for recording an image by applying ink on a recording medium with at least one recording head, comprising:

a timer for measuring a recording downtime when an image-recording operation of the recording head is interrupted during the recording operation and is then resumed; and

control means for performing a temperature control of the recording head before the resumption of the recording operation, in accordance with the length of the recording downtime measured by the said timer,

wherein, with said control means, the number of drive pulses to be applied to the recording head is increased as the recording downtime becomes longer.

2. (Original) The recording apparatus according to Claim 1, wherein interruption of the recording operation during an image-recording operation is executed midway through a recording operation of a continuous image.

3. (Original) The recording apparatus according to Claim 1, wherein, with the temperature control, an electrothermal conversion member disposed in the recording head is heated to the extent of not causing ink in the recording head to be discharged therefrom.

4. (Currently amended) The recording apparatus according to Claim 1, further comprising a temperature sensor for detecting a temperature of the recording head, wherein, with ~~the~~ said control means, the recording head is heated before the resumption of the recording operation up to a temperature of the recording head detected by ~~the~~ said temperature sensor before the interruption of the recording operation and is further heated in accordance with the length of the measured recording downtime.

5. (Currently amended) The recording apparatus according to Claim 1, further comprising a temperature sensor for detecting temperatures of the recording head before and after the interruption of the recording operation, wherein, with ~~the~~ said control means, the temperature control of the recording head is performed before the resumption of the recording operation in accordance with detected temperatures before and after the interruption of the recording operation and is further performed in accordance with the length of a recording downtime detected thereafter.

6. (Currently amended) The recording apparatus according to Claim 1, wherein ~~said~~ the at least one recording head comprises a plurality of recording heads for

different recording ink colors, and with ~~the~~ said control means, the temperature control of each of the plurality of recording heads for the different recording ink colors is performed in accordance with the measured length of interruption of the recording operation.

Claim 7 (cancelled)

8. (Currently amended) A control method of a recording apparatus for recording an image by applying ink on a recording medium with at least one recording head, comprising the steps of:

measuring a recording downtime with a timer when an image-recording operation of the recording head is temporally interrupted during the recording operation and is then resumed; and

performing a temperature control of the recording head before the resumption of the recording operation in accordance with the length of the recording downtime measured by the timer,

wherein, in the step of performing the temperature control of the recording head, the number of drive pulses to be applied to the recording head is increased as the recording downtime becomes longer.

9. (Original) The control method according to Claim 8, wherein interruption of the recording operation during an image-recording operation is executed midway through a recording operation of a continuous image.

10. (Currently amended) The control method according to Claim 8, wherein, in the step of performing ~~a heating~~ the temperature control of the recording head, an electrothermal conversion member disposed in the recording head is heated to the extent of not causing ink in the recording head to be discharged therefrom.

11. (Currently amended) The control method according to Claim 8, further comprising the step of detecting a temperature of the recording head, wherein, in the step of performing ~~a heating~~ the temperature control of the recording head, the recording head is heated before the resumption of the recording operation up to a temperature exceeding that detected by a temperature sensor before the interruption of the recording operation, and an extent to which the temperature exceeds that before the interruption of the recording operation varies in accordance with the length of the measured recording downtime.

12. (Currently amended) The control method according to Claim 8, further comprising the step of detecting a temperature of the recording head, wherein, in the step of performing ~~a heating~~ the temperature control of the recording head, the recording head is heated before the resumption of the recording operation up to a temperature detected by a temperature sensor before the interruption of the recording operation and is further heated in accordance with the measured recording downtime.

13. (Currently amended) The control method according to Claim 8, further comprising the step of detecting temperatures of the recording head before and after the interruption of the recording operation, wherein, in the step of performing ~~a heating~~ the temperature control of the recording head, the temperature control of the recording head is performed before the resumption of the recording head in accordance with detected temperatures of the recording head before and after the interruption of the recording operation and is further performed in accordance with the length of a recording downtime detected thereafter.

14. (Currently amended) The control method according to Claim 8, wherein ~~said the~~ at least one recording head ~~is~~ comprises a plurality of recording heads for different recording ink colors, and, in the step of performing ~~a heating~~ the temperature control of the plurality of recording heads for the different recording ink colors, the heating control of each recording head is performed in accordance with the measured length of interruption of the recording operation.

Claim 15 (cancelled)